

## Appendix D Index

Numerals before and after colons designate chapters and pages respectively (for example, 4:6 designates page 4-6). Italicized numerals indicate that the subject is illustrated in a figure.

Abrasion, 7:1; 9:1-2  
control, 2:6; 4:8-9

Abrasiveness, 3:8

ABS  
see Acrylonitrile butadiene styrene pipe

Absorption, 9:1-2

Acrylonitrile butadiene styrene pipe, 5:1, 3, 9-10

AASHTO, 2:9; 5:5

Air relief valves, 11:1, 3, 4, 5

Air vents, 2:11; 8:7

Allowable stress, 2:6; 3:5, 15-17; 4:14, 16

Allowable pressure, maximum, 2:7; 3:2, 4-6; 4:9

Allowance, corrosion-erosion, 3:4-5, 15-16

Aluminum, 3:2; 4:10, 12, 20-21  
alloys, 4:20-21

Ambient temperature, 3:17, 28

American National Standards Institute, 2:5; 3:17, 19;  
11:1

American Petroleum Institute, 2:5; 4:10

American Society of Mechanical Engineers, 2:5; 3:17, 19;  
4:14

American Society for Quality Control, 2:5

American Society for Testing and Materials, 2:5; 3:1; 5:2

American Water Works Association, 2:8-9; 3:19; 4:17;  
11:1, 7

Anchors  
for fiberglass pipe, 7:4

ANSI  
see American National Standards Institute

API  
see American Petroleum Institute

ASCE 7, 2:8

ASME Boiler and Pressure Vessel Code

ASME B31, Code for Pressure Piping, 11: 5-6  
B31.1, Power Piping, 3:4-5  
B31.3, Chemical plant and petroleum refinery piping,  
2:8-9; 3:2-3, 15, 17-19; 5:2; 11:6-7

ASME Standards for  
cast iron pipe flanges and flanged fittings, 4:14  
factory-made wrought steel butt welding fittings, 4:14  
pipe flanges and flanged fittings, 4:14  
welded and seamless wrought steel pipe, 4:14

ASTM  
see American Society for Testing and Materials

Atmospheric vacuum breaker, 11:1, 3

Austenitic stainless steel, 4:18

AWWA  
see American Water Works Association

Backflow prevention, 10:1; 11:7-8

Ball Valve, 10:8, 11  
V-port, 10:11

Bedding factors, 5:5, 7, 8

Bending, 3:16

Bill of materials, 3:21

Bleed-off of air, 11:1, 3-5

EM 1110-1-4008  
5 May 99

Bolting, 3:19-21, 23; 9:2-3  
Torque, 3:23; 9:4-5

Bolting Materials, 3:21

Brass pipe, 4:21

Brazed joints, 4:10

Brinell Hardness, 3:1

Brittle transition temperature, 3:1, 29

Butterfly valve, 2:15; 10:8, 12, 16-17, 21-22

Cable leak detection systems, 8:8

CADD

see Computer-aided drafting design

Calculations, 2:1

Carbon steel pipe, 4:17-18; 8:3; 9:1-3  
specifications, 4:17

Category D fluid service, 3:31; 11:6

Category M fluid service, 11:6  
sensitive leak test, 3:31

Cathodic protection, 1:1; 4:1, 3-4, 6; 9:1; 12:1-2, 3, 4  
design, 12:2  
impressed current system, 12:3  
galvanic protection, 12:3  
isolation joints, 4:3; 12:2,4

Caulked joints, 4:10

Cavitation, 4:8-9

Charpy impact test, 3:1

Check valve, 2:15; 10:9-10, 21

Chemical resistance; 7:5

Chlorinated polyvinyl chloride pipe (CPVC), 5:1, 3,  
4, 10  
support spacing for, 5:7

Coatings, protective,  
for piping, 12:4  
for supports, 3:30

Codes, 2:5-6  
organizations, 2:5

Coefficient of expansion, 2:9

Component standards, 2:6

Compression molding, 7:1

Computer-aided drafting design (CADD), 2:10

Computer programs

CADD, 2:10

heat tracing, 11:12

pipeline design and analyses, 2:1, 10

pipe networks, 3:4

stress analysis, 3:17

valve selection, 10:20

Concentration cell, 4:1

Construction Engineering Research Laboratories,  
USACE (CERL), 4:1-2

Copper and copper alloy pipe, 4:21  
support spacing for, 4:10,13

Corrosion, 2:6; 4:1-9  
allowance, 3:4-5, 15-16  
coatings, 4:1; 12:4  
concentrated cell, 4:1, 3-4, 5  
dealloying, 4:1, 8  
erosion corrosion, 4:1, 8-9  
external, 7:1; 9:1; 12:1  
galvanic, 4:1-3  
general, 4:1-2  
intergranular, 4:1, 6  
internal, 4:4, 6, 8-9; 7:1; 9:1; 12:1  
microbially induced, 4:9  
pitting, 4:1, 4, 6  
protection, 4:1, 4, 6; 12:1-4  
stress-corrosion cracking, 4:1, 7; 5:1; 8:1; 9:1-2  
theory of, 4:1

Corrosion expert, qualifications, 4:1; 12:1-2

- Corrosion resistance, 3:1, 26; 4:2, 17-18; 5:1-2; 6:2; 7:1; B:1
- Cost, 3:1, 8; 7:1; 10:13
  - preliminary for system design, 2:2
- Couplings, 2:15; 9:2; 11:1
  - Dresser, 11:2
- CPVC
  - see Chlorinated polyvinyl chloride pipe
- Cracks, 4:7; 8:1
- Critical closure time, 3:6-7
- Critical pressure ratio, 10:17, 19
- Damage, physical, 2:6
- Darcy-Weisbach
  - equation, 3:8-9
  - friction factor, 3:8-9, 11, 14
  - loss coefficients, 3:8-9, 13
- Dead weight, 2:7
- Deflection, 2:6; 3:25-26; 5:5
  - lag factor, 5:8
- Deformation, 3:1; 8:2; 12:4
- Design
  - bases, 2:2, 5, 10
  - conditions, 2:5
  - criteria, 2:1,6
  - factors, 9:1-2
  - flow rate, 3:7-14
  - pressure, 2:5,7
    - external, 2:7
    - internal, 2:7
  - pressure integrity, 3:5, 7, 14-17
  - specifications, 2:1
  - system descriptions, 2:1
  - temperature, 2:5, 7
- Diaphragm valve, 10:8, 21-22
- Differential pressure, 10:13, 14-15, 17, 20
- Dimensional standards, 7:1
- Dissimilar materials, interconnection of, 2:6; 4:2-3; 9:2
- Dissolved gases, 3:3
- Double check valve backflow preventer, 11:7-8
- Double containment piping, 8:1-8, 9:1
  - regulatory basis for, 8:1
  - standards, 8:1
- Drain, 2:11; 8:6-7; 11:5
- Drain valve, 11:5
- Drawing generation, 2:1-2, 3-4, 10, 12-13
- Dresser couplings, 11:2
- Drop-weight impact test, 3:1
- Ductile iron pipe, 4:17
- Ductility, 3:1
- Dynamic loads, 2:7
- Elasticity, 3:1, 6; 8:6
- Elastomeric piping, 6:1-5
  - connections, 6:4
  - corrosion resistance, 6:2-3
  - liners, 9:7
  - standards, 6:2
  - temperature limits, 6:1
- Elastomeric seals, 7:2
- Elastomeric seats, 10:1, 6
- Electrical isolation, 12:2, 4
- Elongation, 3:1; 4:14
- Environmental factors, 2:6
- Environmental stress cracking, 5:2; 8:1; 9:1
- Equivalent length of piping, 3:8-9, 12

EM 1110-1-4008  
5 May 99

Erosion, 2:6; 3:15; 10:13

Erosion corrosion, 4:1, 8-9

Excess pressure, due to water hammer, 3:5-7

Excursions, pressure/temperature, 2:7; 3:3, 5-7

Expansion, 2:8; 11:9

fluid, 11:7

thermal, 2:8, 10; 4:14; 7:4-5; 8:2, 4, 6; 9:3

Expansion-contraction, 2:10; 7:4; 8:2, 6

Expansion joints, 4:15; 5:3; 7:4; 8:2, 6; 9:3; 11:11

ball, 11:9-10

bellows, 4:15; 5:3; 11:1, 9-10

corrugated, 11:1, 10

slip, 4:15; 5:3; 11:9

Expansion Loop, 2:12; 4:15-17; 5:3-4; 7:1, 4-5; 8:2, 5,  
6

Fatigue, 3:15, 18-19

Fiberglass, 7:1; 10:8

Filament winding, 7:1-2

Fittings, 2:6; 4:14

cast bronze/brass, 4:21

flanged, 4:17-20

threaded, 4:17-20

malleable iron, 4:17

nickel alloy, 4:20

steel, 4:17-19

thermoplastic, 5:2, 9-10

welding, 4:15, 17-20

butt welding, 4:14, 18

socket welding, 4:14, 18

Flammable fluids, 3:2

Flange, 3:2, 19-20; 7:2; 10:7

facings, 3:20

materials, 3:19

ratings, 3:2

selection and limitations, 3:19-20

thermoset, 7:2

Flanged joints, 2:15; 3:2, 19-20; 4:14; 9:2

Flexible connections, 2:15, 12; 3:26; 11:1

Flexibility, 2:12, 15; 4:15; 7:1; 8:2, 6

Flow, 3:7-14; 9:1

characteristic for valves, 10:1, 2, 3

coefficient, 3:9; 10:13, 15, 16, 17, 20

drainage, 8:7

flushing, 8:7

rate, 3:7; 10:1

resistance coefficient, 3:9

velocity, 3:8

Flushing, system, 3:30-31; 8:7

Friction factor-turbulent flow, 3:8, 9, 10

Friction loss, 3:8

FRP

see Fiberglass reinforced plastic

Galvanic action, dissimilar joints, 4:2-3

Galvanic protection for supports, 3:29

Galvanic series, 4:2

Galvanizing, 4:17

Gaskets, 3:19-22; 9:2

Gate valve, 10:11, 21

Glass, glass-lined pipe, 9:7

Glass pipe, 8:3

Globe valve, 10:10-11, 16, 21-22

Hangers, 2:9, 3:26

Hardness, 3:1

Hardy Cross method, 3:14

Hastalloy, 3:2; 4:19

- Hazardous applications, 10:10
- Hazardous substance, 8:1, 8
- Hazardous wastes, 9:1
- Hazen-Williams formula, 3:19
  - coefficient, 3:9-10
  - limitations, 3:14
- HDPE, 5:11
- Head loss, 3:8
- Heat-tracing, 2:10; 8:6; 9:1, 3; 11:12
  - design consideration, 2:10; 8:6
- Hydraulic conditions, backpressure, 3:2
- Hydraulic diameter, 8:6-7
- Hydraulic loads, 2:9
- Hydraulic snubber, 10:9
- Hydrostatic testing, 2:11; 3:30
  - test pressure, 3:30
- Ice load, 2:8
- Identification of piping, 3:23-24
- Impact
  - failure, 7:1
  - strength, 3:1
  - test, 3:1
- Inconel, 4:19-20
- Installation
  - above ground, 5:5; 6:5; 8:6; 9:3; 12:1
  - below ground, 5:5, 9; 6:5; 7:4; 8:6; 9:3; 12:1
  - leak detection systems, 8:8
  - reduced pressure backflow prevention assemblies,  
11: 7-8
  - supports, 3:25; 9:3
- Insulation
  - electrical isolation, 3:29; 12:2, 4
  - thermal, 2:10; 3:25-27; 8:6; 9:3; 11:10
- Insulation thickness, 3:25
- Intergranular attack, 4:6
- Internal piping, 1:1
- International Organization for Standardization, 2:5; 5:2
- ISO
  - see International Organization for Standardization
- Isolation
  - joints, 12:2,4
  - of supports for reinforced polyester pipe, 7:3
  - valves, 10:1, 11, 13
- Isometric drawings, 2:1, 14
- Joining, thickness allowance, 3:15
- Joints, piping, 4:10, 14
  - brazed, 4:10
  - caulked, 4:10
  - compression, 4:10
  - compression couplings, 11:1
  - coupled, 11:1
  - DIP, 4:14
  - flanged, 2:15; 3:2, 19-20; 4:14; 7:2; 9:1; 10:7
  - flared, 4:10
  - gasketed, 3:19-22
  - grooved, 3:15, 4:20
  - inspection, 3:29
  - mechanical, 4:18, 20; 9:2
  - metallic, applicable codes, 4:14
  - screwed, 10:7
  - soldered, 4:10, 14
  - swagging, 3:15
  - thermoplastic, 5:2-3
  - thermoset, 7:1-2
  - threaded, 3:15; 4:10, 14, 20; 5:9
  - welded, 3:29; 4:10, 14; 10:7
- Laminar flow, 3:8, 10
- LDPE, 5:11
- Leak detection, 8:1, 8
- Leak-testing, 3:29-31
  - methods, 3:29-31

EM 1110-1-4008  
5 May 99

- planning, 3:29
  - records, 3:29-30
  - sensitive leak test, 3:31
- Leakage
- expansion joints, 11:9
  - valve seats, 10:7
- Length equivalents, 3:8, 11
- Lift check valve, 10:9-10
- Liner, pipe, 7:1; 9:1-2
- liquid applied, 9:6
  - material properties, 9:6
- Lined piping, 9:1-7
- elastomeric/rubber, 9:7
  - glass, 9:8
  - nickel, 9:8
  - PFA, 9:3, 7
  - PP, 9:2-7
  - PTFE, 9:2-7
  - PVDC, 9:3-7
  - PVDF, 9:2-7
- Live load, 2:7-10
- Loading conditions, 2:6-10
- dead load, 2:7
  - live load, 2:7-10
  - occasional load, 2:7-10
  - sustained load, 2:7; 3:19
- Malleable iron, 4:17
- Manning factors, 3:9-10, 14
- Manufacturer Standardization Society of the Valve and Fitting Industry (MSS), 2:5; 3:28, 29; 4:14
- Martensitic stainless steel pipe, 4:18-19
- Material combinations
- double containment piping, 8:1-3
  - valve seat, 10:4-5
- Material selection guidelines, B:1
- MDPE, 5:11
- Mechanical joints, 4:18, 20
- Minor loss coefficients, 3:8, 12
- Modulus of elasticity, 3:1; 7:1
- Modulus of soil reaction, 5:9
- Monel, 3:2; 4:19
- Moody diagram, 3:8, 10
- Reynolds number, 3:8, 10
- MSS
- see Manufacturer Standardization Society of the Valve and Fitting Industry
- National Fire Protection Association, 11:12
- National Institute of Standards and Technology (NIST), 2:5
- NFPA
- see National Fire Protection Association
- Nickel and nickel alloys, 4:10-11, 19-20
- liner, 9:7
- NIST
- see National Institute of Standards and Technology
- Nominal pipe size, 1:2
- Nominal thickness, 1:2
- NPS
- see Nominal pipe size
- Operators, valve
- electric, 10:8-9
  - hydraulic, 10:8-9
  - manual, 10:8
  - pneumatic, 10:8-9, 21
  - schedule, 10:20, 22
- Over pressure protection, 3:4-5
- Piping and instrumentation diagrams (P&ID), 2:1-2, 4, 9; 4:14-15; 5:2; 10:13

Permeability, 9:1-2

Personnel protection, 8:7

PFD see Process flow diagram

Pinch valve, 10:12

## Pipe

acrylonitrile butadiene styrene, 5:1, 3, 9-10  
aluminum, 3:2; 4:10, 12, 20-21  
brass, 4:21  
carbon steel, 4:17-18; 8:3; 9:1-3  
chlorinated polyvinyl chloride, 5:1, 3, 4, 7, 10  
copper, 4:10, 13, 21  
ductile iron, 4:17  
ductility, 3:1  
fiberglass, 7:1  
glass, 8:3  
glass-lined, 9:7  
joints, 3:15; 4:10, 14; 5:2-3; 7:1, 4  
identification, 3:23-24  
liners, 7:1; 9:1-7  
material selection, 3:1-2  
nickel, 4:10-11, 19-20  
polyethylene, 5:1, 5, 10-11  
polypropylene, 5:1, 3, 10-11  
polyvinyl chloride, 5:1, 3-4, 6, 9  
pressure, 2:7; 3:2-7  
red brass, 4:21  
steel  
  carbon, 4:9-10, 17-18; 8:3; 9:1-3  
  stainless, 3:2; 4:9-10, 18-19  
strength, 3:1  
stress, 2:1  
  allowable, 2:6; 3:5, 15-17; 4:14, 16  
  code limits, 2:6  
  combined longitudinal, 3:17, 19; 4:16; 8:2, 6  
  external pressure, 3:15  
  internal pressure, 3:15-17  
supports, 2:1, 9-10, 15; 3:17, 23-28, 29, 20; 7:3-4; 8:6  
  drawings, 2:1  
  types, 3:29  
thermal expansion, 2:7-8, 10; 4:14; 7:4-5; 8:2, 4, 6;  
  9:3  
thermoplastic, 5:1-11  
thermoset  
  reinforced epoxy, 7:1-5  
  reinforced furan, 3:2; 7:1-2, 4-5  
  reinforced polyester, 7:1-5

reinforced vinyl ester, 7:1-2, 4-5  
sizing, 3:1, 7-14; 5:2; 8:6-7  
sizing criteria, 3:8  
standard sizes, 1:1-2; 3:16  
tolerances, 3:15-16  
toughness, 3:1  
wall thickness, 2:6-7; 3:5, 14-17; 7:4

## Piping

accessibility, 2:11  
codes and standards, 2:5-6  
double containment piping, 8:1-8; 9:1  
feedwater, 3:3-7  
flexibility, 2:10, 12  
heat tracing, 8:6; 9:1, 3; 11:12  
instrumentation diagram (P&ID), and, 2:1-2, 4, 10;  
4:14-15; 5:2; 10:13  
insulation, thermal, 2:10; 3:25-27; 8:6; 9:3; 11:10  
interferences, 2:10  
layout considerations, 2:2, 10, 13-14, 15; 3:17  
material selection, 3:1-2  
metallic, 4:1-21; 8:3  
network, 3:8, 14  
physical sketches, 2:2  
pump, 2:10, 15; 3:3-5  
rack, 2:9; 3:27  
relief valve, 3:4-5, 16-17, 29; 11:5-6  
specifications, 2:1  
supports, 2:1, 9-10, 15; 3:17, 23-29; 7:3-4; 8:6  
  drawings, 2:1  
system, 1:1  
thermoplastic pipe and fittings, 5:1-11; 8:3  
thermoset piping and fittings, 7:1-7; 8:3  
vents and drains, 3:29  
wall thickness, 2:6-7; 3:5, 14-17; 7:4

## P&IDs

see Piping and instrumentation diagrams

Piping components, 2:1-2, 6; 3:2-3, 19

Piping fatigue, 3:15, 18-19

Piping system design, 2:1-15  
  sizing criteria, 3:8

Plant layout, 2:2, 10, 12-14, 15; 3:17

Plasticization, 5:1

EM 1110-1-4008  
5 May 99

Plug valve, 10:12

Pneumatic testing, 3:30-31  
design pressure, 3:31

Polyester fiberglass pipe, 7:3-5

Polyethylene (PE), 5:1, 5, 10-11

Polypropylene (PP), 5:1, 3, 10-11  
liner, 9:2, 6

Polytetrafluoroethylene (PTFE), 5:1, 9  
liner, 9:2-3, 6-7  
valve packing, 10:8

Polyvinyl chloride (PVC), 5:1, 3-4, 6, 9  
supports spacing for, 5:6

Polyvinylidene fluoride (PVDF), 5:1, 10-11  
supports spacing for, 5:6  
liner, 9:2-3, 6-7

Positioner, for valve, 10:9, 21-22

PP  
see Polypropylene

Predesign survey, 2:2,5; 12:2

Pressure, 3:2-7; 9:1  
class, 3:19-20  
design, 3:2-4  
drop, 3:7-8; 10:1, 13, *14-15*; 11:8  
head, 3:8  
integrity, 3:1, 14-17, 19  
internal, 2:7; 3:2-3, 7, 17; 7:4  
maximum steady state, 3:2  
rating, 3:5, 20; 5:2; 7:5; 10:1  
surges, 7:1  
tests, 3:29-31  
transients, 2:7; 3:3-8; 4:9  
wave, 3:5-7

Pressure, maximum allowable, 2:7; 3:2, 4; 4:9

Pressure relief devices, 11:5-7  
for double containment piping, 8:7  
for pneumatic testing, 3:30

Pressure-temperature rating, 3:3, 19

Pressure variation, transients, 2:7; 3:3-7; 4:9

Pressure wave, 3:5-7

Probe leak detection system, 8:8

Process control, 2:1-2, 4

Process flow diagrams (PFD), 2:1-2, 3; 4:14-15; 5:2; 7:4

Protective coatings  
for piping, 4:1; 12:4  
for supports, 3:29

PTFE  
see Polytetrafluoroethylene

Pump  
installation piping, 2:10, 15  
system curves, 10:13-14

PVC  
see Polyvinyl chloride

PVDF  
see Polyvinylidene fluoride

Qualification  
of welders, 3:29  
of welding procedures, 3:29

Quality, 2:1

Rack piping, 2:10; 3:27

Reduced pressure backflow preventer, 11:7-8

Reduction of area, 3:1

Reinforcement, 7:1

Relief valves, 3:4-5, 16-17, 29; 11:5-6

Resins, 7:1

Restrained design, 8:2,6

- Reynolds number, 3:8, 10, 13; 10:13, 17, 18
- RMA  
see Rubber Manufacturers Association
- Rockwell hardness, 3:1
- Rotary shaft valve, 10:8-9, 21-22
- Roughness, 3:8-9; 7:1
- Route selection, 2:10-11
- Rubber Manufacturers Association, 6:2
- Rupture disk, 11:6-7
- SAE  
see Society of Automotive Engineers
- Safety codes, 2:7
- Sample connections, 11:5
- Sample piping, 11:5
- Saran, 9:6
- SD see System description
- SDR  
see Standard dimension ratio
- Seismic  
codes, 2:6,8-9  
loads, 2:8-9  
zones, 2:8
- Selection criteria  
piping materials, 3:1-2  
valves, 10:1-3
- Self-contained automatic valve, 10:12-13
- Sensitive leak test, 3:31
- Sizing  
air and vacuum relief devices, 11:3  
drain, 8:7  
piping, 3:7-14
- rupture discs, 11:6-7  
thermoplastic pipe, 5:2  
valves, 10: 13, 14-15, 16-17, 18-19, 20
- Slurry, 9:2; 10:12
- Snow load, 2:8
- Society of Automotive Engineers, 6:1-2
- Soil conditions, 2:5; 12:2  
modulus of soil reaction, 5:8
- Specifications, 2:1
- Stainless steels, 3:2  
austenitic, 4:18  
ferritic, 4:18-19  
martensitic, 4:18-19
- Standard dimension ratio (SDR), 3:6
- Standards, 2:5-6; 7:1-2  
dimensional, 7:1, 5
- Static mixers, 11:8-9  
pressure loss, 11:8
- Steel  
carbon, 4:17-18; 8:3; 9:1-3  
stainless, 3:2; 4:18-19  
austenitic, 4:18  
ferritic, 4:18  
martensitic, 4:18
- Stop check valve, 10:9-10
- Storage tank piping, 8:1
- Strain, 3:1, 18
- Strength  
tensile, 3:1; 7:1  
yield, 3:1, 29-30; 8:1
- Stress  
allowable, 2:6; 3:5, 15-17; 4:14, 16  
combined longitudinal, 3:17, 19; 4:16; 8:2, 6  
cracking, 8:1; 9:1-2  
design, 2:5; 9:1-2

EM 1110-1-4008

5 May 99

- external loads, 3:15
  - pressure, 3:3, 5; 8:2, 6
  - relieving, 4:7
  - thermal, 4:14-16; 5:3; 7:4; 8:2
- Stress analysis, 3:1, 17-19
- for seismic excitation, 3:19
  - for thermal expansion, 3:18
  - for weight, 3:17
- Structural attachments, 2:9; 3:25, 27
- Structural integrity, 3:25; 7:3
- Supports, piping, 2:1, 8-9, 11; 3:17, 23-28, 29, 30; 7:3-4; 8:6
- adjustment, 3:30
  - ambient systems, 3:17, 29
  - attachments piping, 3:29
  - attachments to building, 2:9; 12:4
  - coatings, protective, 3:30
  - cold spring, 3:30
  - cold systems, 3:27
  - design of (general), 2:9-10; 3:23
  - dynamic loadings, 2:9
  - hot systems, 3:27
  - installation of, 3:23
  - interstitial, 8:6
  - load determination, 3:25-26
  - loading considerations, 2:9-10; 4:14
  - locating supports, 2:9-10; 3:23, 25
  - materials, special considerations, 4:10
  - pump interconnection, 2:9-10, 15
  - rod hangers, 2:9; 3:26, 29
  - rollers, 3:26-27, 29
  - saddles, 3:27, 29
  - seismic loadings, 2:8-9
  - selection, of, 3:23, 28, 29, 30
  - spacing of supports, 2:9; 3:23, 25-26; 4:9-10; 5:4; 7:3-4
  - spring hangers, 3:26-27, 29; 5:4
  - temporary, 3:29-30
  - valves and fittings, 3:15; 10:9
  - vibration dampers, 2:9
- Supports and support spacing
- for double containment piping, 8:6
  - for elastomeric piping, 6:5
  - for metallic piping, 4:9-14
- for thermoplastic piping, 5:5-7
  - for thermoset pipe, 7:3-4
- Surge control
- electrical, 12:4
  - pressure, 2:9
- Survey, Predesign, 2:2, 5; 12:2
- Swing check valve, 10:9-10, 21
- System, description, 2:1
- Temperature, 9:1; 10:1
- brittle fracture, 3:29; 7:1
  - design, 3:2
  - limits,
    - for fiberglass pipe, 7:1-2, 5
    - for thermoplastic liners, 9:1
  - transition, 3:1, 29
- Thermal analysis
- allowable offset span in, 7:4
  - free thermal, 7:4
  - thermal modes, 7:4
- Thermal expansion, 2:7, 9; 4:14; 7:4-5; 8:2, 4, 6; 9:3
- Thermoplastic piping, 5:1-11
- available products, 5:1
  - dimensioning systems, 5:2
  - jointing methods, 5:2-3
  - pressure rating, 5:2
- Thermoplastics, 5:1-11
- liners, 9:1-2
  - spacers, 9:2
- Thermoset pipe, 7:1-6
- Thermosetting resins, 7:1
- Tilting disc check valve, 10:9-10
- Tolerances, 3:15-16
- Toughness, 3:1
- Turbulent flow, 3:8, 10

- Ultimate tensile strength, 3:1
- Uniform Building Code
  - seismic loads, 2:8
- UPS, 8:8
- Vacuum breaker, 11:1, 3, 4, 5
  - location, 11:5
- Valve
  - air relief, 11:1, 3, 4, 5
  - angle, 10:11, 16
  - back-flow prevention, 10:1
  - ball, 10:8, 11
  - bleed-off of air, 11:1, 3-5
  - blow-off, 11:5
  - butterfly, 2:15; 10:8, 12, 16-17, 21-22
  - check, 2:15; 10:9-10, 21
  - control, 10:13-20
  - diaphragm, 10:8, 21-22
  - drain, 11:5
  - gate, 10:11, 21
  - globe, 10:10-12, 16, 21-22
  - isolation, 10:1, 11, 13
  - location design, 2:15
  - maintenance of, 10:11
  - pinch, 10:12
  - plug, 10:13
  - pressure rating, 10:1
  - pressure relief valves, 3:4-5; 11:5-6
  - recovery factor, 10:13, 15, 16-17, 20
  - regulating, 10:1
  - relief, 10:1
  - selection, 10:20
  - standards, 2:6
  - stem leakage, 10:7
  - supports, 3:15; 10:9
- Valve location, 2:15
- Vent, 2:11; 9:1,3
  - extension, 9:3
- Vibration, 2:9; 5:5
- Vinyl-ester fiberglass pipe, 7:4-5
- Visual leak detection system, 8:8
- Wafer valve, 10:7-8, 11-12
- WHAMO, 3:6
- Wall relaxation, 8:2
- Wall thickness, 2:6-7; 3:5, 14-17; 7:4
  - corrosion allowance, 3:15-16
- Water hammer, 2:8, 15; 3:5-8, 17; 7:1; 11:7
- Weight, system, 2:7
- Welders, qualification of, 3:29
- Welding
  - procedure specification, 3:29
  - tests, 3:29
- Welds, examinations of, 3:29
- Wheel load, 2:9-10; 7:4
- Wind load, 2:8
- Yield strength, 3:1, 29-30; 8:1