

INDEX

A

- Air admission at culvert filling valves, 8-19, 9-8, 9-26
- Arkansas River, 8-2 (*see also* Dardanelle Lock and Dam; Robert S. Kerr Lock and Dam; Lock and Dam 17, Verdigris River)
 - additional contraction, 10-3
 - cofferdams, 8-32
 - construction sequence, 10-2, 10-3
 - cutoff, typical, 10-11
 - dikes, typical system, 10-10
 - dredging, 10-2
 - initial dredging, 10-3
 - maintenance dredging, 10-3, 10-4
 - annual volumes, 10-12
 - cumulative volume, 10-4
 - function of discharge, 10-14
 - policy, 10-4
 - Pool 2, 10-3, 10-4
- hinged pool operation (*see* Hinged pool operation)
- locks, 8-22, 9-2
 - costs, 11-3
 - discharge manifolds with baffles, 8-51
- navigation dams, 7-1
- navigation project, 10-10, 10-11
 - project plan, 10-11
- pool characteristics, 10-3, 10-4
- sediment load, 10-2
- spillway piers, 7-5
- submerged dikes in upper lock approach, 9-2

B

- Barkley Lock, 8-16
- Bay Springs Lock, Tennessee-Tombigbee Waterway, 8-7, 8-23, 8-55, 9-6, 9-7, 9-8
 - canal surge, 9-7
 - construction, 8-34

- downstream canal design, 9-7
- emptying time, 9-7
- filling time, 8-23, 8-24
- floor culverts, 8-23
- hawser stresses, 8-23, 9-7
- intake design, 9-8, 9-25
- layout, 9-21
- lock emptying time, 8-23, 9-7
- outlet system, 9-7
- valve opening time, 9-7
- vortex action, 9-8
- Bottom longitudinal floor culverts (*see* Longitudinal floor culverts)

C

- Canal surges, 9-4
 - amplitude
 - Bay Springs, Tennessee-Tombigbee Waterway, 9-7
 - Verdigris River, 9-8
- Canalization, 1-2, 3-1
 - Arkansas River, 10-2
 - Ohio River, 7-2, 11-1, 11-17
 - physical constraint, 2-1
 - planning, 2-1
 - economic studies, 2-1
 - evaluating existing streams, 2-1
 - locks, 2-2
 - navigation equipment 2-1
 - physical constraints, 2-1
 - tow size, 2-2
 - views of users, 2-2
 - Red River Waterway, B-1
 - Upper Mississippi River, 10-14, 11-1, 11-18
- Channel width (*see* Navigation channel, width)
- Choteau Lock and Dam (*see* Locks, Lock and Dam 17, Verdigris River)
- Cofferdams, 8-2, 8-29, 8-30, 8-31, 8-32
 - Dardanelle Lock and Dam, Arkansas River, 8-2, 8-32

- Lock and Dam 26 replacement, Mississippi River, 8-2, 8-31
- passing navigation traffic, 8-2
- problems during project construction, 8-2
- Smithland Locks and Dam, Ohio River, 8-2, 8-30
- stages of construction, 8-2
- Construction
 - cofferdams, 8-2
 - off-channel (in the dry), 8-2, 8-33
 - Dardanelle Lock and Dam, Arkansas River, 8-2
 - materials availability, 8-3
 - Melvin Price Locks and Dam, Mississippi River, 8-2
 - Red River Locks and Dams, 8-2, 8-33
 - site access, 8-3
- Construction materials, 8-3
- Corps of Engineers
 - Inland Waterways System, 1-1
 - innovative lock design, 11-3
- Cross currents
 - effect on navigation, 8-1
- Culverts (*see* Lock culverts, Lock filling and emptying systems)
- Currents
 - cross currents, 8-1, 9-2, 9-3
 - hazardous currents, 5-3
 - lower lock approach, 8-21
 - ports in lower guard wall, 9-2
 - ports in upper guard wall, 9-1, 9-2
 - upper approach, Dardanelle Lock, 9-2
- Cutoffs
 - Arkansas River, 10-11
 - Red River Waterway, B-1

D

- Dams
 - classification by head, 3-1
 - low-head dams, 7-1
 - wickets, 7-7
- Dardanelle Lock and Dam, Arkansas River, 8-2, 8-22, 9-2
 - baffles, 8-22
 - cofferdams, 8-32
 - deposition in lower lock approach, 9-9
 - filling time, 8-22
 - hawsér stresses, 8-22
 - intake ports, 8-44
 - longitudinal floor culverts, 8-53
 - ports in guard walls, 9-2

- sediment, 10-2
- submerged dikes in upstream lock approach, 9-2
- trashracks, 8-44
- wing dike in lower approach 9-9
- Depth
 - minimum depth, 5-1
- Dikes
 - Arkansas River, 10-10
 - Red River Waterway, B-3, B-7
 - submerged in upper lock approach, 9-2
 - Lock and Dam 2, Red River, 9-2
 - Arkansas River locks, 9-2
- Discharge manifolds, 8-49, 8-50, 8-51 (*see also* Lock emptying systems)
- Dissolved oxygen levels, 7-2 (*see also* Reaeration)
- Double lockage (*see* Lockage time, double lockage)
- Dredged material disposal
 - disposal areas, 10-9
 - problems, 10-9
- Dredging, 10-1
 - advance maintenance dredging, 10-2
 - aperiodic dredging, 10-1
 - Arkansas River (*see* Arkansas River, dredging) at heads of pools, 4-4
 - costs, 10-1
 - environmental impacts, 10-1
 - initial construction dredging, 10-1
 - maintenance dredging, 10-1
 - effect of hinged pool operation, 10-7
 - effect of reservoir operation, 10-2
 - Mississippi River, 10-5
 - Missouri River, 10-6
 - objectives, 10-1
 - overdepth dredging, 10-1, 10-2
 - new construction dredging, 10-1
 - periodic dredging, 10-1
 - priorities, 10-1
 - production rate, 10-1
 - Red River, 10-6
 - selecting disposal method and site, 10-1
 - selecting dredging method, 10-1
- Dredging equipment
 - discharge lines, 10-8
 - floating lines, 10-8
 - shore lines, 10-8
 - hydraulic pipeline (suction) dredges, 10-7, 10-8, 10-17, 10-18
 - cutterhead, 10-8, 10-18
 - dustpan, 10-8, 10-18
 - plain suction, 10-8
 - sidecasting, 10-8

- hopper dredges, 10-8, 10-16
- mechanical dredges, 10-7, 10-16
 - bucket dredges, 10-7
 - dipper dredges, 10-7

Drift angle of tow, 5-5

E

Eddies in lower lock approach, 9-4

Emergency lock closure (*see* Lock closure facilities)

F

Fish, migratory

- mitigation measures, 6-2

Flood releases

- tapering off, 10-2

- rate of flow reduction, 10-2

Flood stage

- effect on dam height, 6-1

- hinged-pool operation, 6-1

Flows limiting navigation, 9-1, B-1

G

Gallipolis Locks and Dam, Ohio River

- innovative lock design, 11-1

- intake manifold, 8-45, 8-46

- vortex action, 8-18

Gates (*see* Spillway gates; Lock gates)

Gate sills (*see* Lock gates, gate sills)

Greenup Locks, Ohio River, 8-21, 9-1, 8-40

H

Hazards (*see* Navigation hazards)

Hawser forces, 8-13, 8-19, 8-20

- Bay Springs Lock, Tennessee-Tombigbee Waterway, 9-7

- Dardanelle Lock, 8-22

- disturbances causing, 8-13

- limiting criteria, 8-13

- model data, 8-13

Head

- reverse head, 8-6, 8-8

High-lift locks, 8-22

- Bay Springs Lock, Tennessee-Tombigbee Waterway, 8-23

- bottom longitudinal systems, 8-22

- filling and emptying systems, 8-22

- Lower Granite Lock, Snake River, 8-22

Hinged pool operation, 6-4, 10-2

- Arkansas River, 1995 floods, 10-7

- design factors, B-4

- effect on maintenance dredging, 10-7

- Red River Waterway, B-3, B-8

- Locks and Dams 3, 4, and 5, B-8

Hinged spillway crest, 7-2, B-9

Hydropower at navigation dams, 6-3

- flow available for generation, 6-3

I

Ice

- accumulation on barges, 8-8

- passing ice at navigation projects, 7-5

- Upper Mississippi River, 7-5

Illinois River, 7-4

Inland waterways system in U.S., 1-4, 11-7

Innovative lock design (*see* Locks, innovative design)

Intake manifolds (*see* Lock intake manifolds)

K

Kanawha River, 8-5, 11-4, 11-5

L

Lift (*see* Lock lift)

Lockage time

- delays, 11-1, 11-4

- double lockage, 11-1, 11-6

Lock approach conditions, 5-3, 9-2, 9-3, 9-4

- Bay Springs Lock, Tennessee-Tombigbee Waterway, 9-7, 9-23

- Dardanelle Lock, Arkansas River, 9-2, 9-10, 9-31

dikes

- submerged, 9-2

- contraction B-7

- eddies in lower approach, 9-4

- fill along shore line, 9-3

- guide and guard walls, 5-3, 9-31

- Lock and Dam 1, Red River Waterway, B-2, B-7

- Lock and Dam 2, Red River Waterway, 9-2, 9-11, B-2, B-7
- Lock and Dam 17, Verdigris River, 9-8, 9-27, 9-28, 9-29, 9-30
- Lock and Dam 52, Ohio River, 9-4, 9-18
- Olmsted Lock, Ohio River, 9-4, 9-16, 9-17
- Red River Waterway, B-2, B-3, B-7
- Robert S. Kerr Lock, Arkansas River, 9-3, 9-12, 9-13, 9-14, 9-15
- sediment deposition (*see* Shoaling in lock approaches)
- shoaling (*see* Shoaling in lock approaches)
- sight distance, 9-1
- spur dikes, B-3, B-7
- Lock capacity
 - increasing lock capacity, 11-2, 11-3
 - Lock and Dam 26, Mississippi River, 11-2
 - Melvin Price Locks and Dam, Mississippi River, 11-2
 - Winfield Locks and Dam, Kanawha River, 11-4
- Lock chamber size, 8-3
- Lock closure facilities
 - emergency closure, 8-24, 8-25
 - facilities, 8-25
 - sills, 8-8
 - Marmet Lock, Kanawha River, 11-5
 - Ohio River locks, 8-25
 - overhead vertical lift gates, 8-25
 - potential losses, 8-24
 - sector gates, 8-25
 - submergible gates, 8-25
 - stop logs, 8-25
 - maintenance closure, 8-24
 - Arkansas River locks, 8-24
 - low-lift lock facilities, 8-24
 - submergible gates, 8-24
- Lock culverts (*see also* Longitudinal floor culverts)
 - air entrainment, 8-19, 9-8
 - air vent size, 9-8
 - control valves, 8-18, 8-47
 - tainter gates, 8-18
 - valve opening times 8-19, 8-47
 - intakes, 8-18 (*see also* Lock intake manifolds)
 - surges, 9-8
 - wall culverts
 - bulkheads, 8-19
 - side-port systems, 8-19
 - unwatering, 8-19
- Lock emptying systems, 8-21, 8-49, 8-50, 8-51, 8-52 (*see also* Lock filling and emptying systems)
 - baffles, 8-22
- Bay Springs Lock, Tennessee-Tombigbee Waterway, 9-22, 9-24
 - common river outlet for two locks, 8-22, 9-4
 - emptying in lower approach, 8-21, 8-49, 8-50, 9-1
 - emptying riverward of locks, 8-21, 8-22, 8-49, 8-52, 9-1
- Greenup Lock, Ohio River, 8-49, 8-52
 - lateral diffuser systems, 8-49, 8-50
 - Greenup Locks, Ohio River, 8-21, 8-49
- McArthur Lock, St. Mary's River, 8-21, 8-49
- New Cumberland Locks, Ohio River, 8-21, 8-50
- Olmsted Locks, Ohio River, 8-52, 9-4
- Saint Anthony Falls Lower Lock, Mississippi River, 8-21, 8-50
- Snell Lock, St. Lawrence Seaway, 8-21, 8-49
- Lock emptying time, 8-39, 9-7
- Lock filling and emptying systems, 8-4, 8-5, 8-12, 8-15 (*see also* Lock emptying systems; Locks, innovative lock design)
 - baffles, 8-51
 - incremental valve opening, 8-15
 - longitudinal floor culverts, (*see* Longitudinal floor culverts)
 - loop culverts, 8-14
 - low-lift locks, 8-40
 - modern systems, 8-15 (*see also* Lock filling and emptying systems, Longitudinal floor culverts)
 - over, between, around lock gates, 8-14
 - sector gates, 8-14
 - tainter gates, 8-14
 - stub culverts, 8-14, 8-40
 - TVA multiport system, 8-20
 - valves in gates, short culverts, 8-14
 - wall culverts and bottom lateral systems, 8-15, 8-40
 - wall culverts and ports or laterals, 8-15
 - early conventional systems, 8-15
 - wall culverts and port systems, 8-15, 8-19, 8-40
 - port/culvert area ratio, 8-23
 - port design criteria, 8-19
 - port elevation, 8-19
 - port length, 8-19
- Lock filling systems (*see* Lock filling and emptying systems)
- Lock filling time, 8-41, 8-47
 - improved tow haulage system, 11-6
 - innovative design, 11-6
 - prototype-model relationship, 8-38

- Lock floor, 8-6
 - uplift, 8-6
 - elevation criteria, 8-6
 - stabilization of foundation, 8-6
- Lock gates, 8-6, 8-34
 - design load, 8-6
 - emergency closure, 8-8, 8-25
 - gate opening time, 5-4
 - gate sills, 8-6, 8-34
 - depth/draft ratio, 8-8
 - effect of ice on clearance, 8-8
 - sill clearance, 8-7
 - sill elevation, 8-7, 8-8
 - Temporary Lock 52, Ohio River, 9-4
 - lift gates, 8-8
 - miter gates, 8-6, 8-8, 8-35
 - operation, 8-6
 - sector gates, 8-8, 8-14, 8-37
 - submergible gates, 8-36
 - tainter gates, 8-8, 8-14
 - tidal channels, 8-8
 - types, 8-6
- Lock intake manifolds, 8-16, 8-17, 8-18
 - Bay Springs Lock, Tennessee-Tombigbee Waterway, 8-42
 - bulkheads, 8-17
 - Dardanelle Lock, Arkansas River, 8-44
 - Gallipolis Locks, Ohio River, 8-45, 8-46
 - head loss coefficients, 8-43
 - Ice Harbor Lock, Snake River, 8-42
 - innovative design, 11-3
 - passing drift and ice, 8-16
 - port/culvert area ratio, 8-16
 - port size, 8-16
 - port throat area, 8-16
 - Saint Anthony Falls Lower Lock, Mississippi River, 8-42
 - Siamese intakes, 8-16, 8-40
 - submergence, 8-17
 - trash racks, 8-17, 8-44
 - unwatering, 8-17
 - upper gate sill intakes, 8-16, 11-3, 11-5
 - vortex action, 8-17
- Lock lift, 3-1, 8-4
 - high-lift locks, 3-1, 8-22
 - intermediate lift locks, 3-1, 8-4
 - low lift locks, 3-1, 8-4
- Lock walls, 8-9, 8-34
 - approach walls, 8-11, 8-12
 - ports to reduce cross currents, 9-2
 - types, 8-12
 - culvert discharge walls, 8-11
 - culvert intake walls, 8-10
 - gate bay walls, 8-10, 8-11
 - guard walls, 5-3, 8-11, 9-2
 - ports, 9-2
 - guide walls, 5-3, 8-11, 9-3
 - flow distribution through ports, 9-3
 - Lock and Dam 1, Red River Waterway, B-2, B-6
 - Lock and Dam 2, Red River Waterway, 9-2, 9-3, B-2, B-6
 - Lock and Dam 3, Red River Waterway, B-2
 - ports, 9-3
 - Robert S. Kerr Lock, Arkansas River, 9-3
 - height, 8-5, 8-9, 8-10, B-1
 - Red River Waterway, B-1
 - lock chamber walls, 8-10
 - sight distance, 8-1
 - types, 8-4, 8-12
 - criteria, 8-4
 - walls categorized by purpose, 8-9
 - wall port systems, 8-16, 8-19 (*see also* Wall ports)
 - port design criteria 8-19
 - port elevation 8-19
 - port length, 8-19
- Locks
 - approach conditions (*see* Lock approach conditions)
 - access during floods, 8-10
 - Bay Springs Lock, Tennessee-Tombigbee Waterway, 8-23, 8-55
 - Bankhead Lock, Black Warrior River, Alabama, 8-54
 - classification by lift, 3-1
 - closure during floods, 8-9
 - combination type, 8-5
 - costs, 11-3, 11-6
 - cushion of water, 8-5, 8-19
 - Dardanelle Lock and Dam, Arkansas River, 8-22
 - depth, 8-5, 8-6
 - sill elevation, 8-6
 - tow squat, 8-7
 - design criteria, 8-3
 - lock size, 8-3
 - number of locks, 8-3
 - dimensions in United States, 8-3
 - double lockage 11-1, 11-6
 - Winfield Locks and Dam, Kanawha River, 11-4
 - dry-dock type, 8-4, 8-5

- filling criteria, 8-19
- filling time, 8-5, 8-13
 - optimum filling time, 8-8
- Greenup Locks, Ohio River, 8-21, 9-1
- hazardous approach conditions, 9-1
- innovative lock design
 - Corps of Engineers test program, 11-3
 - culverts on lock floor, 11-3
 - faster valve operating speed, 11-6
 - guide and guard walls, 11-4
 - improved tow haulage system, 11-6
 - Marmet Lock and Dam, Kanawha River, 11-4, 11-5
 - McAlpine Lock and Dam, Ohio River, 11-4, 11-5
 - Monongahela No. 4 Lock and Dam, 11-4, 11-5
 - Mississippi River locks, 11-4, 11-5
 - need for, 11-3
 - thin lock chamber walls, 11-3
 - Winfield Locks and Dam, Kanawha River, 11-4, 11-5
- intake manifolds (*see* Lock intake manifolds)
- floor (*see* Lock floor)
- gates (*see* Lock gates)
- gravity locks, 8-4
- guard walls, 5-3 (*see also* Lock approach walls)
- guide walls, 5-3 (*see also* Lock approach walls)
- Kanawha River, 8-5, 11-4, 11-5
- lift, 5-3, 8-4 (*see also* Lock lift; High-lift locks; Medium-lift locks; Low-lift locks)
- location, 8-1
 - criteria, 8-1, 9-1
 - channel width, 9-1
 - cross currents, 8-1, 9-1
 - sediment transport and deposition, 9-9
 - sight distance, 8-1, 9-1
- lockage time, 3-2, 11-6
- Lock and Dam 17, Verdigris River, 9-8
- Lock and Dam 26, Mississippi River, 11-2
- Lock and Dam 26 replacement, Mississippi River, 8-28
 - cofferdams, 8-31
- Lower Granite Lock and Dam, Snake River, 8-22, 8-41
- Olmsted Locks and Dam, Ohio River, 7-2, 8-22, 9-1, 9-4
- Melvin Price Locks, Mississippi River, 8-1
- mooring facilities, 8-12
- multiple locks, 8-3
- number of locks, 8-3
- operation, 3-2, 3-3
- Panama Canal Locks, 8-11
- Red River Waterway, B-1
 - Lock and Dam 1, B-2, B-3, B-6
 - Lock and Dam 2, B-2, B-6
 - Lock and Dam 3, B-2, B-4
 - Lock and Dam 4, B-4
 - Lock and Dam 5, B-4
- reinforced concrete locks, 8-4
- reverse head, 8-6, 8-8, 8-14
- Saint Anthony Falls Locks, Mississippi River, 8-8
 - Saint Anthony Falls Lower Lock
 - lock miter gates, 8-35
 - submersible tainter gate, 8-36
- sills (*see* Lock gates, gate sills)
- size, 3-2
- Snell Lock, Saint Lawrence Seaway, 8-40
- steel sheet piling locks, 8-5
- temporary locks, 8-5
- Temporary Lock 52, Ohio River, 9-4
- "twin locks", 8-1
- types, 8-4
- United States locks, 3-1, 3-2
- walls (*see* Lock walls)
- Locks and dams, 3-1
 - site criteria, 3-1, 4-1, 4-2, 4-3
 - in bends, 8-29
 - layout for low-lift dams, 8-26, 8-27
- Locks and Dams 50 and 51, Ohio River, 8-2
- Longitudinal floor culverts, 8-15, 8-16, 8-53, 8-54, 8-55
 - baffles along walls and between culverts, 8-22, 8-23
 - Bankhead Lock, Black Warrior River, 8-54
 - Bay Springs Lock, Tennessee-Tombigbee Waterway, 8-55
 - combining culverts, 8-23
 - crossover culverts, 8-22, 8-23
 - culvert area ratio, 8-23
 - culvert distribution (location), 8-23
 - Dardanelle Lock, Arkansas River, 8-22, 8-53
 - filling and emptying times, 8-24
 - innovative design, 11-3
 - Lower Granite Lock, Snake River, 8-41
 - model data, 8-24
 - "over and under" system, 8-23, 8-54, 8-55
 - port/distribution culvert area ratio, 8-23
 - port manifold location, 8-23
 - ports, 8-23
 - access for inspection and maintenance, 8-23
 - size, 8-23

"side by side" system, 8-22, 8-53

Low-head dams

- flow regimes, 7-3, 7-10
- lock and dam layout, 8-27
- overflow embankments, 7-2
- spillways, 7-2
 - swellhead, 7-2
- typical cross section, 4-4

Low-lift locks, 3-1

- filling and emptying systems, 8-15, 8-16
- layout, 8-27

Lower Granite Lock, Snake River, 8-22

- floor culverts, 8-22

M

Maintenance dredging (*see* Dredging, maintenance dredging)

Maintenance of navigation structures, 11-2

Lock and Dam 26, Mississippi River, 11-2

Marmet Lock and Dam, Kanawha River, 11-4

Marseilles Lock and Dam, Illinois River, 7-4

Mc Alpine Lock and Dam, Ohio River, 11-4

Medium lift locks, 8-1

filling and emptying systems, 8-15, 8-16

Melvin Price Locks and Dam, Mississippi River
(replacement for Locks and Dam 26),
8-1, 8-28, 11-2, 11-3

costs, 11-3

Mississippi River, 8-1, 8-2, 8-15, 11-1

cofferdams, 8-31

dredging, 10-5

flood of 1993, 8-9

ice, 7-5, 8-8

Locks and Dam 26 replacement, Mississippi
River (Melvin Price Locks and Dam),
8-1, 8-28

Melvin Price Locks and Dam, 8-1, 8-28

Saint Anthony Falls locks

discharge laterals, 8-21

Upper lock, 8-35

tainter gates, 8-8

Upper Mississippi River, 7-5

canalization, 10-14, 11-1

traffic, 11-2, 11-8

Mitigation measures

migratory fish, 6-2

Models

Bay Springs Lock, Tennessee-Tombigbee

Waterway

air entrainment, 9-8

canal surge, 9-7

filling and emptying time, 9-7

intake design, 9-8

outlet diffuser design, 9-8

valve operating time, 9-7

vortex action, 9-8

Dardanelle Lock and Dam, 9-2

effect of wing dikes on shoaling in lower
approach, 9-9

innovative design models, 11-3, 11-4

intake models, 11-5

Lock and Dam 2, Red River, 9-2

longitudinal floor culverts

filling time, 8-24

emptying time, 9-7

navigation conditions in lock approaches, 9-2,
9-3

Olmsted Locks outlet works, 9-4

riprap stability at outlet, 9-4

Robert S. Kerr Lock and Dam, Arkansas River,
9-2

spillway models, 7-3

surge conditions, 9-7

tow squat, 9-6

Monongahela River No. 4 Lock and Dam, 11-4,
11-5

Mosquito control, 6-2, 6-5

N

Navigation channel

authorized dimensions, 10-10

overdepth dredging 10-10

width, 5-2, 5-5

width in bends, 5-5

Navigation dams, 7-1 (*see also* Low-head dams)

Arkansas River, 7-1, 7-8

effect of flood heights, 6-1

fixed, 7-1

height, 6-1

movable, 7-1, 7-6, 7-8

About self-tripping wicket, 7-6

bear-trap dam, 7-6

Chanoine wicket, 7-6

Chanoine-Pescaud wicket, 7-6

Olmsted Locks and Dam, Ohio River, 7-7

wicket gates, 7-7

navigable pass, 7-1

Red River, 7-1

site selection affected by location of water
intakes, sewer outfalls, etc., 6-1, 6-2

- spacing, 3-3
- typical low-head dam, 4-4
- wicket gates, 7-1, 7-7
- Navigation development
 - canalized, 1-2
 - canals, 1-2
 - cost sharing, 11-3
 - Federal funding, 11-3
 - in United States, 11-1
 - Mississippi River, 11-1
 - Ohio River, 11-1
 - open-river, 1-2
- Navigation equipment
 - design tow size, United States, 3-2
 - tow size (*see* Tow size)
 - terminals, 5-4
- Navigation locks (*see* Locks)
- Navigation hazards, 9-1
 - currents, 9-1
 - Dardanelle Lock and Dam, Arkansas River, 9-2
 - expansion eddies, 9-1
 - flood stages, 9-1
 - high velocities, 9-1
 - lock emptying system, 9-1
 - lower approach, 9-1
 - Lock and Dam 2, Red River, 9-2
 - power plant discharges, 9-1
 - sediment, 9-1
 - shoaling, 9-1
 - spillway discharges, 9-1
 - surges, 9-1
 - tow squat, 9-1
- Navigation pass, 7-1
- Navigation pool level
 - effects on fish and wildlife, 6-2
 - effects on water supply intakes, 6-1
 - effects on local drainage, 6-1
 - operation for vector control, 6-2, 6-5
- Navigation projects
 - components of projects, 1-3
 - channel width, 5-2
 - criteria for design, 5-1, 5-2, 5-3, 5-4
 - design requirements, 6-1
 - hazardous currents, 5-3
 - hydropower development, 6-3
 - minimum depth, 5-21
 - objectives in developing, 1-1
 - recreation use of navigation pools, 6-3
 - transit time, 5-3
 - terminal facilities, 5-4
 - ways to develop, 1-1
- Navigation structures
 - site selection, 4-1, 4-2, 4-3

New Cumberland Locks, Ohio River, 8-21

O

Ohio River

- canalization, 7-2, 11-1
- Gallipolis Locks vortex action, 8-18
- Greenup Locks, 8-40
- Olmsted Locks and Dam, 7-2, 8-22, 9-1, 9-4
- Smithland Locks, 8-2, 8-30
- Temporary Lock 52, 9-4
- traffic, 11-1, 11-8
- Olmsted Locks and Dam, Ohio River, 7-2, 7-9, 8-22, 9-1, 9-4
 - emptying system, 9-4
 - layout, 7-9
- Open-river spillway operation, 10-3
- Overflow embankments, 7-2

P

Panama Canal Locks, 8-11

Planning

- canalization, 2-1
- project life, 2-1
- site selection, 4-1, 4-2, 4-3

Ports

- deflectors, 8-48
- for 110-ft lock, 8-48
- in approach walls to reduce currents, 9-2
- in upper guard wall, Dardanelle Lock, 9-2
- in upper guide wall, Lock and Dam 2, Red River, 9-2
- TVA multiport system, 8-48

R

Reaeration, 7-2, B-4

Red River Waterway, 7-1, 7-3, 7-4, 9-3, B-1

- costs, 11-3
- hinged crest spillway, 7-2
- hinged pool operation (*see* Hinged pool operation)
- Lock and Dam 1
 - layout, 10-15
 - sediment deposition (*see* Sediment deposition, Red River Waterway)
 - submersible pump, 10-6
- Lock and Dam 2

- ports in upper guide wall, 9-2
- submerged dikes in upstream approach, 9-2
- locks, B-1, B-2
- project description B-1, B-6
- reaeration of spillway discharge, 7-2, B-4
- sediment deposition (*see* Sediment deposition, Red River Waterway)
- sediment load, B-2
- spillways, B-1, B-4, B-5, B-9
 - design optimization, B-4, B-5, B-10
- stilling basins B-1
- Reoxygenation (*see* Reaeration)
- Robert S. Kerr Lock and Dam, Arkansas River, 9-3
 - cross currents, 9-3
 - eddies in lower lock approach, 9-4
 - ports in upper guide wall, 9-3
- Reservoir operating criteria
 - to reduce shoaling, 10-2

S

- Saint Anthony Falls Locks, Mississippi River, 8-8
 - Lower Lock discharge laterals, 8-21
 - tainter gates, 8-8
 - Upper lock, 8-35
 - Vortex action at Lower Lock, 8-17
- Saint Lawrence Seaway, 8-40
 - Snell Lock emptying system, 8-21
- Sector gates (*see* Lock gates, sector gates)
- Sediment deposition (*see also* Shoaling in lock approaches)
 - Red River Waterway
 - at miter gates, 10-6, B-2, B-6
 - drains in sill to prevent, B-2
 - in lock chamber, 10-6
 - Lock and Dam 1, B-2, B-3, B-6
 - 1984, 1-6
 - 1990, 10-6
 - Lock and Dam 2, B-7
- Sheet piling locks, 8-5
- Shoaling in lock approaches, 9-9
 - Dardanelle Lock lower approach, 9-9
 - effect of ports in upstream guide wall, 9-9
 - effect of wing dikes, 9-9
 - in lower lock approach, 9-9
 - in upper lock approach, 9-9
 - minimized by reservoir operation, 10-2
 - minimized by hinged pool operation, 10-7
 - Red River Waterway, B-3
 - Lock and Dam 1, B-3, B-6
- Sight distance (*see* Locks, location)
- Sills (*see* Lock gates, sills)

- Site access for construction and operation, 8-3
- Smithland Locks and Dam, Ohio River, 8-2, 8-30
- Snake River, 8-23 (*see also* Lower Granite Lock)
- Snell Lock, Saint Lawrence Seaway
 - emptying system, 8-21
- Spillways
 - baffled spillway, 7-3, B-4, B-9
 - cross currents at locks, 8-1
 - design optimization, B-4, B-5, B-10
 - flow regimes, 7-3
 - hinged crest, 7-2, B-9
 - hydraulic models, 7-3
 - low-lift navigation dams, 7-2
 - passing ice and debris, 7-3, 7-4, 7-5
 - reaeration, 7-2, B-4
 - Red River Waterway dams, B-1
 - uncontrolled crests, B-1
- Spillway gates
 - flap gates, 7-14
 - hinged crest gates, 7-2, 7-4, 7-14, B-4, B-9
 - Red River Waterway locks and dams, 7-2, B-4
 - roller gates, 7-4, 7-13
 - submersible gates, 7-3
 - Illinois River, 7-4
 - Marseilles Lock, Illinois River, 7-12, 7-13
 - tainter gates, 7-3, 7-11
 - types, 7-3
 - vertical lift gates, 7-4, 7-14
- Spillway piers
 - ogival pier nose, 7-8
 - pier shape, 7-5, 7-8
 - semicircular pier nose, 7-8
- Squat (*see* Tow squat)
- Streamflow
 - maximum navigable flow, 8-9
- Submerged dikes (*see* Dikes)
- Submersible pump to remove sediment, 10-6, 10-7

T

- Tainter gates
 - spillway gates, 7-3, 7-8
 - "reverse" tainter gates in culverts, 8-18
- Tennessee-Tombigbee Waterway, 8-7, 9-6 (*see also* Bay Springs Lock)
 - canal surge, 9-7
- Tennessee Valley Authority
 - filling and emptying systems, 8-15
 - multiport system, 8-20, 8-48
- Terminal facilities
 - site criteria, 5-4

- Towboat power, 9-5, 9-8
 - Kort nozzles, 9-5
 - Ohio River, 9-5
 - Verdigris River, 9-8

- Tow size
 - Arkansas River, 2-2
 - Kanawha River, 11-4
 - Lower Mississippi River, 2-2, 2-3
 - Missouri River, 2-2
 - Ohio River, 11-1
 - Red River Waterway, B-1
 - United States, 3-2
 - Upper Mississippi River, 2-2, 2-3, 11-1
 - Verdigris River, 9-8

- Tow squat
 - effect of lock entering speed, 9-6
 - effect of open emptying valves, 9-6, 9-19, 9-20
 - effect of propeller speed, 9-6
 - types of squat
 - displacement squat, 9-5
 - moment squat, 9-6, 9-19
 - piston squat, 9-5, 9-19
 - propeller squat, 9-6

- Verdigris River
 - effect of channel deepening, 9-9, 9-29, 9-30
 - effect of channel widening, 9-8, 9-30

- Trashracks, 8-17

V

- Valve opening time, 8-47, 9-7, 11-6
 - Bay Springs Lock, Tennessee-Tombigbee Waterway, 9-7

- Vector control, 6-2, 6-5

- Velocities

- in lower lock approach, 9-3
 - limiting navigation B-1

- Verdigris River, 9-8, 9-27

- Vortex action

- Bay Springs Lock, 9-8
 - Gallipolis Locks, Ohio River, 8-18
 - lock intake ports, 8-17
 - model studies, 8-17, 8-18
 - port submergence, 8-17
 - Saint Anthony Falls Lower Lock, 8-17

W

- Walls (*see* Lock walls)

- Wall culverts (*see* Lock filling and emptying systems)

- Wall ports

- design criteria 8-19
 - lock filling time, 8-16
 - port elevation, 8-19
 - port length, 8-19

- Waterborne commerce

- Ohio River, 11-1, 11-8
 - Upper Mississippi River, 11-2, 11-8

- Waterways Experiment Station

- innovative lock design studies, 11-3, 11-4

- Wicket gates (*see* Dams, wickets)